Audio SYSTEM

MZ360145EX

INSTALLATION MANUAL

WARNING

- Read these installation instructions thoroughly prior to starting installation work.
- Wiring should be performed after disconnecting the negative terminal of the battery. Otherwise , it may cause electric shock or physical injury.
- This equipment is specific to vehicles equipped with 12V DC negative ground systems. Do not install it in any vehicle equipped with a 24V system , such as a large truck or diesel powered automobile equipped for cold regions. Such usage causes danger of fire.
- All cords should be kept together to avoid interference with driving operations. It is dangerous if they wind around the steering column , gear shift lever or break pedal.
- If any cord comes in contact with a burr (sharp projection formed during the manufacture of parts) or any other sharp object , protect the cord covering with tape to avoid damage. Any damage to the covering may be a cause of fire or electric shock.
- Never install in a manner that blocks front visibility, interferes with normal driving operations of the steering wheel, gear shift lever or brake pedal or creates a danger to any passenger in the case of a sudden stop. It may be the cause of a traffic accident or injury.
- Be sure to use all the accessory components as instructed and attach them securely. Never use a part other than that specified. Use of such a part may cause danger of damage to the internal components of the unit or loosening or detachment of components.
- When attaching the ground to bolts or nuts attached to the vehicle , never use those of any safety related component such as the steering , brake system or fuel tank. Such usage may cause accidents.
- After completion of the wiring and installation work , ensure that all electric components , such as the brake system, lights , horn and turn signal lights operate normally as before the installation. If operation is not normal , find the cause by checking the wiring to make sure it is proper. Use with unknown problems may be the cause of fire , electric shock and accidents.
- Never disassemble or modify the unit. It may be the cause of accident , fire or electric shock.
- If any abnormality , such as penetration by any foreign material , splashing , smoking or abnormal odors occurs, stop use immediately and contact the dealer you purchased the unit from or a local service shop . Continuing use may be the cause of accidents , fire or electric shock.



- 1 Remove the center air outlet panels. Remove the two screws and remove the center unique panel.
 - \cdot Disconnect the hazard switch connector.



2 Remove the audio unit (4 screws) and bracket (8 screws). Note The removed audio unit will not be used.







4 Connect the connectors (20Pin connector and radio antenna plug) to the Audio unit (A-1). Secure the Audio unit (A-1) using 4 screws.

