

Volvo Car Corporation Gothenburg, Sweden

Instruction No 31414629

Version

Part. No.

31414288 1.0

Battery Charger





IMG-389985

Battery Charger- 31414629 - V1.0 © Volvo Car Corporation




Volvo Car Corporation Gothenburg, Sweden








Volvo Car Corporation Gothenburg, Sweden



IMG-392010



Volvo Car Corporation Gothenburg, Sweden



IMG-398640



Volvo Car Corporation Gothenburg, Sweden

1

Read through all of the instructions before starting installation.

Notifications and warning texts are for your safety and to minimise the risk of something breaking during installation.


Ensure that all tools stated in the instructions are available before starting installation.

Certain steps in the instructions are only presented in the form of images. Explanatory text is also given for more complicated steps.

In the event of any problems with the instructions or the accessory, contact your local Volvo dealer.

Color symbols

2



- 1. Used for focused component, the component with which you will do something.
- Used as extra colors when you need to show or differentiate additional parts.
- 3. Used for attachments that are to be removed/installed. May be screws, clips, connectors, etc.
- Used when the component is not fully removed from the vehicle but only hung to the side.
- 5. Used for standard tools and special tools.
- 6. Used as background color for vehicle components.

IMG-363036

Removal




Volvo Car Corporation Gothenburg, Sweden


3



IMG-394535



IMG-387004




IMG-394520



Volvo Car Corporation Gothenburg, Sweden

6




Remove the screws.

Remove the marked part.

IMG-382828


7



Remove the screws.

Remove the clip.

8



Remove the screws.


Remove the marked part.

IMG-398443 © Volvo Car Corporation



Volvo Car Corporation Gothenburg, Sweden


9



Remove the nuts.

Remove the screw.

10



Remove the screw.


Remove the clips.

IMG-398446



Volvo Car Corporation Gothenburg, Sweden


11



Remove the marked part.


IMG-397073

12



Open the hood.

13



Remove the rubber strip.

© Volvo Car Corporation




Volvo Car Corporation Gothenburg, Sweden

14

Remove the clips.


Remove the marked part.



15

Remove the clips.

Remove the marked part.




16



The screws are to be reused.

Remove the screws.




IMG-391312


© Volvo Car Corporation



Volvo Car Corporation Gothenburg, Sweden



18




Use: Air-powered keyhole saw

Accessory installation




Volvo Car Corporation Gothenburg, Sweden

19



IMG-392258



21



MG-392260

Note!

Note the position.


© Volvo Car Corporation



Volvo Car Corporation Gothenburg, Sweden


22

Pull the wiring through.




IMG-392257

23



IMG-392262

24




Tighten the nut.

© Volvo Car Corporation




Volvo Car Corporation Gothenburg, Sweden

25



26




Install component that comes with the accessory kit.

© Volvo Car Corporation




Volvo Car Corporation Gothenburg, Sweden

27



Note! Orientation view


28



Reinstall the screws.

Tightening torque: M8 , 24 Nm

29



IMG-393832

Install the screws.


Tightening torque:,

© Volvo Car Corporation




Volvo Car Corporation Gothenburg, Sweden

30



Connect the connector.


31



Install the catch.

Press until a click is heard.

32



Tighten the cable ties.

IMG-398641
© Volvo Car Corporation



Volvo Car Corporation Gothenburg, Sweden


33

G X4

Install the cable.

IMG-391771

34




Install the clips as illustrated.

IMG-391783




Volvo Car Corporation Gothenburg, Sweden

35



Install the clips as illustrated.

36




Note!

Orientation view

IMG-391565

37



Release the catches.

Fold marked part to one side.

IMG-391573

© Volvo Car Corporation




IMG-391924

Installation instructions, accessories


Volvo Car Corporation Gothenburg, Sweden



Remove the nut.



Install the cables.




Install the nut.

Tightening torque: ,


© Volvo Car Corporation



Volvo Car Corporation Gothenburg, Sweden



Press until a click is heard.




Install the cable.



Volvo Car Corporation Gothenburg, Sweden

43



Remove the screws.

Remove the marked part.


IMG-391485

44



Remove the nut.

45




Connect the cable.

IMG-391496

© Volvo Car Corporation



Volvo Car Corporation Gothenburg, Sweden



Install the nut.

Tightening torque: M8 , 24 Nm

Installation

47 Reinstall the removed parts in reverse order.