

Volvo Car Corporation Gothenburg, Sweden

Instruction No 31414774 Version 1.3 Part. No. 31399006


Protective plate, beneath the engine



Volvo Car Corporation Gothenburg, Sweden


Special tools	
	981 4112 Drill
	Tool number:981 4112
	Tool description:Drill
	Tool boards:EU99
	951 2782 Rivet nut tool
	Tool number:951 2782
	Tool description:Rivet nut tool
	Tool boards:08

Materials	
Designation	Part number
Rust inhibitor, low viscosity	





Volvo Car Corporation Gothenburg, Sweden



IMG-382674



Volvo Car Corporation Gothenburg, Sweden

Information

1

Read through all of the instructions before starting installation.

Notifications and warning texts are for your safety and to minimise the risk of something breaking during installation.


Ensure that all tools stated in the instructions are available before starting installation.

Certain steps in the instructions are only presented in the form of images. Explanatory text is also given for more complicated steps.

In the event of any problems with the instructions or the accessory, contact your local Volvo dealer.

Color symbols

2



IMG-363036

Note!

This colour chart displays (in colour print and electronic version) the importance of the different colours used in the images of the method steps.

- 1. Used for focused component, the component with which you will do something.
- Used as extra colors when you need to show or differentiate additional parts.
- Used for attachments that are to be removed/installed. May be screws, clips, connectors, etc.
- 4. Used when the component is not fully removed from the vehicle but only hung to the side.
- 5. Used for standard tools and special tools.
- 6. Used as background color for vehicle components.


Removal



3


Installation instructions, accessories

Volvo Car Corporation Gothenburg, Sweden



- 1. Remove the screws.
- 2. Remove the clips.

The part is not to be reused.



Remove the panel.

The part is not to be reused.

Accessory installation



Volvo Car Corporation Gothenburg, Sweden

981-4112

IMG-382659

Warning!


Wear protective gloves.

Warning!


Wear safety goggles.

Drill the holes.

Use special tool: T9814112, Drill



Use: , Rust inhibitor, low viscosity




Note!

Orientation view

© Volvo Car Corporation



Volvo Car Corporation Gothenburg, Sweden




Use special tool: T9512782, Rivet nut tool

Reset the tool.


IMG-372305

9



IMG-367096

10




Use hands only.

The outermost thread of the tool should be flush with the rivet nut end.

IMG-367098 © Volvo Car Corporation




Volvo Car Corporation Gothenburg, Sweden



Press the tool against the surface.

Hold the tool at right angles to the surface.

IMG-372295




Tighten to the value stated.



Volvo Car Corporation Gothenburg, Sweden

13




Measure

Use: Vernier caliper

IMG-373060


14



Note!

Orientation view

IMG-393378



Note!

Do not fully tighten the bolts.


Install component that comes with the accessory kit.

© Volvo Car Corporation



Volvo Car Corporation Gothenburg, Sweden

16




Note!

Do not fully tighten the bolts.

Install the screws.


11010-3979



Tighten the bolts.

Tightening torque: M8 , $24\ Nm$

....



Tighten the bolts.

Tightening torque: M8 , 24 Nm

© Volvo Car Corporation



Volvo Car Corporation Gothenburg, Sweden